


# Safety Data Sheet



## 1. PRODUCT AND COMPANY IDENTIFICATION:

**PRODUCT NAME:** 1257

**MANUFACTURER:** Selectrode Industries, Inc.  
230 Broadway  
Huntington Station, NY 11746 U.S.A.  
Phone: 631-547-5470  
Fax: 631-547-5475  
E-mail: [info@selectrode.com](mailto:info@selectrode.com)

**EMERGENCY TELEPHONE NUMBER:** 631-547-5470

## 2. HAZARD IDENTIFICATION:

**Emergency Overview:** This product is normally not considered hazardous as shipped. Avoid eye contact or inhalation of dust from the product. When this product is used in a welding process, the most important hazards are welding fumes, heat, radiation and electric shock.

### Classification of the Substance/Mixture

#### CLP/GHS Classification (1272/2008):

Skin Irritation, Category 2

Eye Irritation, Category 2

Carcinogenicity, Category 2

Hazardous to the Aquatic Environment – Acute Hazard, Category 1

#### EU Classification (67/548/EEC):

Harmful (Xn), Irritant (Xi), Carcinogen Category 3, R40, R36/38

#### Hazardous Classification per 29CFR 1910.1200 (Rev. July 1, 2012):

Skin Irritation, Category 2

Eye Irritation, Category 2

Carcinogenicity, Category 2

Hazardous to the Aquatic Environment – Acute Hazard, Category 1

### Labelling:

**Symbols:** Three red diamond-shaped hazard symbols: a person with a star on their chest (Health Hazard), an exclamation mark (Irritant), and a dead tree and fish (Environment).

**Signal Word:** Warning

### Hazard Statements:

**H315** – Causes skin irritation.

**H319** – Causes serious eye irritation.

**H351** – Suspected of causing cancer.

**H400** – Very toxic to aquatic life

### Precautionary Statements:

**P201** – Obtain special instructions before use.

**P202** – Do not handle until all safety precautions have been read and understood.

**P264** – Wash skin and hair thoroughly after handling.

**P273** – Avoid release to the environment.

**P280** – Wear protective gloves/eye protection/face protection.

**P281** – Use personal protective equipment as required.

**Safety  
Data  
Sheet**



**P302+P352** – IF ON SKIN: Wash with plenty of soap and water.

**P304+P340** – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**P305+P351+P358** – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P308+P313** – IF exposed or concerned: Get medical advice/attention.

**P332+P313** – IF skin irritation occurs: Get medical advice/attention.

**P337+P313** – IF eye irritation persists: Get medical advice/attention.

**P362** – Take off contaminated clothing and wash before reuse.

**P391** – Collect spillage.

**P405** – Store locked up.


**P501** – Dispose of contents/container in accordance with local/regional/national/international regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS:**

Chemical Identity	CAS #	Range %	OSHA PEL (mg/m3)	ACGIH-TLV (mg/m3)	Carcinogenicity	EU Classification (67/548/EEC)	CLP/GHS Classification (1272/2008)	Hazardous Classification per 29CFR 1910.1200 (Rev. July, 2012)
Calcium Carbonate	1317-65-3	1-11	5 ( as CaO )	10	No	Not Dangerous	Not Hazardous	Not Hazardous
#Chromium	7440-47-3	20-30	1.0 (Metal) .05 (Cr II & Cr III Compounds) 0.005(Cr VI Compounds) 0.01 ( Cr VI Insoluble Compounds)	0.5 ((Metal) 0.5 (Cr III Compounds) 0.05(Cr VI Soluble Compounds)	Yes	Not Dangerous	(H400) Aquatic Acute 1	(H400) Aquatic Acute 1
Feldspar	68476-25-5	1-11	NR	NR	No	Not Dangerous	Not Hazardous	Not Hazardous
Calcium Fluoride	7789-75-5	1-5	2.5 ( as F )	2.5 ( as F )	No	(Xi) R36/37/38	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A (H335) STOT SE 3	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A (H335) STOT SE 3
Graphite	7782-42-5	1-5	15 (total dust)	2	No	(Xi) R36/37	(H319) Eye Irrit.. 2A (H335) STOT SE 3	(H319) Eye Irrit.. 2A (H335) STOT SE 3
Bentonite	1302-78-9	1-11	NR	NR	No	Not Dangerous	Not Hazardous	Not Hazardous
Carbon	7440-44-0	1-5	15	10	No	Not Dangerous	Not Hazardous	Not Hazardous
Iron Oxide	1317-61-9	1-11	15	10	No	(Xi) R36/37/38	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A (H335) STOT SE 3	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A (H335) STOT SE 3
Titanium Dioxide	13463-67-7	1-11	15	10	No	Carc. Cat. 3  (Xn) R40	(H351) Carc. 2	(H351) Carc. 2
Potassium Silicate	1312-76-1	1-11	NR	5	No	(Xi) R36/38	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A	(H315) Skin Irrit.. 2 (H319) Eye Irrit.. 2A
Sodium Silicate	1344-09-8	1-11	NR	5	No	(C) R34 (Xi) R37	(H314) Skin Corr. 1B (H335) STOT SE 3	(H314) Skin Corr. 1B (H335) STOT SE 3
Silicon	7440-21-3	1-11	5 (as SiO2)	3 (as SiO2)	No	(F) R11	(H228) Flam. Sol. 2	(H228) Flam. Sol. 2



**Safety  
Data  
Sheet**



Requirements (EN Levels)	Type A	Type B
Abrasion (Cycles)	2 (500)	1 (100)
Cut (Factor)	1 (1.2)	1 (1.2)
Tear (Newton)	2 (25)	1 (10)
Puncture (Newton)	2 (60)	1 (20)
Burning Behaviour	3	2
Contact Heat	1	1
Convective Heat	2	-
Small Splashes	3	2
Dexterity	1 (11)	4 (6.5)

Type B gloves are recommended when high dexterity is required as for TIG welding, while type A gloves are recommended for other welding processes. The contact temp (°C) is 100 and the threshold time (seconds) >15.

**Eyes protection:** Welder's helmet or face shield with colour absorbing lenses. Shield and filter to provide protection from harmful UV radiation, infra-red and molten metal approved to standard EN379. Filter shade to be a minimum of shade 9.

**Skin protection:** Heat-resistant protective clothing. Wear safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry. Clothing should be selected to suit the level, duration and purpose of the welding activity.

Class 1	
Impact of Spatter	15 Drops
Heat Transfer (radiation)	RHTI 24 ≥ 7 seconds
Process	<p>Manual welding with light formation of spatter and drops</p> <ul style="list-style-type: none"> <li>• Gas Welding</li> <li>• TIG Welding</li> <li>• MIG Welding</li> <li>• Micro plasma welding</li> <li>• Brazing</li> <li>• Spot Welding</li> <li>• MMA Welding (with rutile-covered electrode)</li> </ul>
Environmental Conditions	<p>Operation of machines</p> <ul style="list-style-type: none"> <li>• Oxygen cutting machines</li> <li>• Plasma cutting machines</li> <li>• Resistance welding machines</li> <li>• Machines for thermal spraying</li> <li>• Bench welding</li> </ul>

Class 2	
Impact of Spatter	25 Drops
Heat Transfer (radiation)	RHTI 24 ≥ 16 seconds
Process	<p>Manual welding with heavy formation of spatter and drops</p> <ul style="list-style-type: none"> <li>• MMA welding (with basic or cellulose-covered electrodes)</li> <li>• MAG welding (with CO2 or mixed gases)</li> <li>• MIG Welding (with high current)</li> <li>• Self-shielded flux core arc welding</li> <li>• Plasma cutting</li> <li>• Gouging</li> <li>• Oxygen cutting</li> <li>• Thermal spraying</li> </ul>

**Safety  
Data  
Sheet**



<b>Environmental Conditions</b>	<p style="text-align: center;"><b>Operation of machines</b></p> <ul style="list-style-type: none"> <li>• In confined spaces</li> <li>• At overhead welding/cutting or in comparable constrained positions</li> </ul>
---------------------------------	--

**9. PHYSICAL AND CHEMICAL PROPERTIES:**

- Appearance:** Solid.
- Color:** Dark Grey
- Odour:** Odourless
- Odour Threshold:** Not Available
- pH Value:** Not Available
- Melting Point/Melting Range:** 1560 - 2000° F, 850 - 1100° C
- Freezing Point:** Not Available
- Boiling Point/Boiling Range:** Not Available
- Flash point:** Not Available
- Evaporation Rate:** Not Available
- Self-in flammability:** Not Available
- Explosion limits:** Not Available
- Vapour pressure:** Not Available
- Vapour density:** Not Available
- Density at 20°C:** Not Available
- Relative density:** 6-9 g/cm<sup>3</sup>
- Solubility:** Insoluble in water.
- Partition coefficient:** Not Available
- Auto-ignition temperature:** Not Available
- Decomposition temperature:** Not Available
- Other Information:** No available data.

**10. STABILITY AND REACTIVITY:**

- Chemical Stability:** This product is stable under normal conditions.
- Hazardous Reactions:** Contact with chemical substances like acids or strong bases cause generation of gas.
- Conditions to Avoid:** This product is stable under normal conditions.
- Incompatible Materials:** Reacts with acid.
- Hazardous Decomposition Products:** When this product is used in a welding process, hazardous decomposition product would include those from volatilization, reaction or oxidation of the material listed in section 3 and those from the base metal and coating. The amount of fumes generated from this product varies with welding parameters and dimensions. Refer to applicable national exposure limits for fume compounds, including those exposure limits for fume compounds found in section 3. Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quality of fumes and gases produced.

**11. TOXICOLOGICAL INFORMATION:**

- Signs and Symptoms of Overexposure:** Inhalation of welding fumes and gases can be dangerous to your health. Classification of welding fumes is difficult because of varying base materials, coatings, air contaminants and processes. The Internal Agency for Research on Cancer has classified welding fumes as possible carcinogenic to humans (Group 2B).
- Acute Effects:** Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes. May cause sensitisation by skin contact

LD/LC50 Values that are relevant for classification
---

**Safety  
Data  
Sheet**



<b>Calcium Carbonate 1317-65-3</b>		
Oral	LD50	>2000 mg/kg (rat)
Inhalation	LC50	>3 mg/L/4hr. (rat)
Dermal	LD50	>2000 mg/kg (rat)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Chromium 7440-47-3</b>		
Oral	LD50	19.8 mg/kg (rat) (Highly Toxic)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Calcium Fluoride 7789-75-5</b>		
Oral	LD50	>2000 mg/kg (rat)
Inhalation	LC50	>5070 mg/m <sup>3</sup> /4 hr. (rat)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Carbon 7440-44-0</b>		
Intravenous	LD50	440 mg/kg (mouse)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Iron Oxide 1317-61-9</b>		
Oral	LD50	>10000 mg/kg (rat)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Titanium Dioxide 13463-67-7</b>		
Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Silicon 7440-21-3</b>		
Oral	LD50	3160 mg/kg (rat)

<b>LD/LC50 Values that are relevant for classification</b>		
<b>Iron 7439-89-6</b>		
Oral	LD50	30000 mg/kg (rat)

**Chronic Effects:** Overexposure to welding fumes may affect pulmonary function and eyes. Prolonged inhalation of titanium dioxide (Classified by 2B by IARC) above safe exposure limits can cause cancer.

**12. ECOLOGICAL INFORMATION:**

**Toxicity:** Welding rods contain metals which are considered to be very toxic towards aquatic organisms. Finely divided welding rods are therefore considered harmful to aquatic organisms.

**Persistence and Degradability:** The welding rods consist of elements that can not degrade any further in the environment.

**Bio accumulative Potential:** Welding rods contain heavy metals which bio accumulates in the food chain. The following figures are the bio concentration factor (BCF) for the substances on their own.

BCF:

Chromium, BCF: 200

Carbon, BCF: 0.14

Iron, BCF: 140000

**Safety  
Data  
Sheet**



**Mobility in Soil:** Welding rods are not soluble in water or soil. Particles formed by working welding rods can be transported in the air.

**Other Adverse Effects:** In massive form, welding rods present no hazards to the aquatic environment. Welding materials could degrade into components originating from the materials used in the welding process. Avoid exposure to conditions that could lead to accumulation in soils or groundwater. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**13. DISPOSAL CONSIDERATIONS:**

**Product:** For product elimination, consult recycling companies or appropriate local authority.  
**USA RCRA:** Unused products or product residue containing chromium is considered hazardous waste if discarded, RCRA ID Characteristics Toxic Hazardous Waste D007.  
 Residue from welding consumables and processes could degrade and accumulate in soils and groundwater.  
**Package:** May be disposed in approved landfills provided local regulations are observed.

**14. TRANSPORT INFORMATION:**

**UN-number:** Welding rods are not classified as dangerous goods for transport and has no UN number.  
**UN proper shipping name:** Welding rods are not classified as dangerous goods for transport and has no UN proper shipping name.  
**Transport hazard class:** Welding rods are not classified as dangerous goods for transport.  
**Packing group:** There are not any special precautions with which a user should or must comply or be aware of in connection with transport or conveyance either within or outside premises.  
**Environmental hazards:** Welding rods are not environmentally hazardous according to the criteria of the UN Model Regulations (as reflected in the IMDG Code, ADR, RID and AND) and/or a marine pollutant to the IMDG Code.  
**Special precautions for users:** There are not any special precautions which a user should or must comply or be aware of in connection with transport or conveyance either within or outside premises of the welding rod.  
**Transport in Bulk According to Annex III MARPOL 73/78 and the IBC Code:** Welding rods in massive form do not subject under MARPOL 73/78 and the IBC Code. Not applicable – product is transported only in packaged form.

**15. REGULATORY INFORMATION:**

**Safety, health and environment regulations/legislation specific for the substance or mixture:** Read and understand the manufacturer’s instructions, your employer’s safety practices and the health and safety instructions on the label. Observe any federal and local regulations. Take precautions when welding and protect yourself and others.  
**Warning:** Welding fumes and gases are hazardous to your health and may damage lungs and other organs. Use adequate ventilation. Electric shock can kill. Arc rays and sparks can injure eyes and burn skin. Wear correct hand, head, eye and body protection.  
**Chemical safety assessment:** No  
 USA: Under the OSHA Hazard Communication Standard, this product is considered hazardous.  
**CALIFORNIA PROPOSITION 65:** **WARNING:** This product contains chemicals including [Titanium Dioxide, Chromium], which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).  
**CALIFORNIA PROPOSITION 65:** **WARNING:** This product can expose you to chemicals including [Chromium], which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). (California Health & Safety Code § 25249.5 et seq.)  
 United States EPA Toxic Substance Control Act: All constituents of this product are on the TSCA inventory list or are excluded from listing.  
**EPCRA/SARA Title III Toxic Chemicals**  
 The following metallic components are listed as SARA 313 “Toxic Chemicals” and potential subject to annual SARA reporting. See Section 3 for weight percentage.

Ingredient Name	Disclosure Threshold
Chromium	1.0 (Metal)

**Safety  
Data  
Sheet**



**16. OTHER INFORMATION:**

The information in this document is believed to be correct as of the date issued. However, no warranty is expressed to be implied regarding the accuracy or completeness of this information. This information and product are furnished on the condition that the person receiving them shall make his own determinations as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

This Material Safety Data Sheet complies with the EC directives 91/155/EEC and 93/112/EEC, including modifications 2001/58/EC.

Complies with OSHA Communication Standard 29 CFR 1910.1200 and Superfund Amendments and Reauthorization Act (SARA) of 1986 Public Law 99-499

**Hazard Statements:**

- H228** – Flammable solid
- H314** – Causes severe skin burns and eye damage.
- H315** – Causes skin irritation.
- H319** – Causes serious eye irritation.
- H335** – May cause respiratory irritation.
- H351** – Suspected of causing cancer.
- H400** – Very toxic to aquatic life

**R-Phrases:**

- R11** – Highly flammable
- R34** – Causes burns.
- R36/37** – Irritating to eyes and respiratory system.
- R36/37/38** – Irritating to eyes, respiratory system and skin.
- R36/38** – Irritating to eyes and skin.
- R37** – Irritating to respiratory system.
- R40** – Limited evidence of a carcinogenic effect.

**S-Phrases:**

- S22** – Do not breathe dust.
- S26** – In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S36/37/39** – Wear suitable protective clothing, gloves and eye/face protection.
- S45** – In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

End of the document.